

ISO Proof Coil Chain - G30

General Purpose/Anchor Chain



ISO Proof Coil Chain is low carbon steel general purpose/anchor chain with an ISO short pitch link. It is used in applications where high tensile strength is not required.

Finish: Hot Dip Galvanized Packaging: Full Drums, Half Drums, and Pails

Exceeds NACM, RR-C-271D specifications

Trade Size in.	Wire Diameter		Inside Dimensions				Working Load Limit	
	mm	in.	Length		Width		kg-force	pound-force
			mm	in.	mm	in.		
3/16	5.5	0.218	24.64	0.97	10.16	0.4	363	800
1/4	7	0.276	25.4	1.00	12.7	0.5	590	1300
5/16	8.4	0.329	28.45	1.12	12.7	0.5	862	1900
3/8	10	0.394	31.24	1.23	15.75	0.62	1202	2650
1/2	13	0.519	38.1	1.50	20.57	0.81	2041	4500
5/8	16	0.630	48.26	1.90	25.65	1.01	3130	6900
3/4	20	0.781	55.88	2.20	27.69	1.09	4808	10600

Trade size in.	Plastic Pail					Half Drum					Full Drum				
	Weight		Length		Part ID	Weight		Length		Part ID	Weight		Length		Part ID
	kg	lbs	m	ft.		kg	lbs	m	ft.		kg	lbs	m	ft.	
3/16	47	102	76.2	250	10312737	148	327	243.84	800	10312727	297	654	487.68	1600	10313036
1/4	46	101	42.98	141	10312738	130	287	121.92	400	10312742	260	574	243.84	800	10313037
5/16	43	95	28.04	92	10312739	129	284	83.82	275	10312743	258	568	167.64	550	10313038
3/8	44	96	19.2	63	10312740	138	305	60.96	200	10312744	277	611	121.92	400	10313039
1/2	44	96	10.97	36	10312741	121	266	30.48	100	10312745	241	531	60.96	200	10313040
5/8	-	-	-	-	-	-	-	-	-	-	264	582	45.72	150	10313041
3/4	-	-	-	-	-	-	-	-	-	-	261	576	30.48	100	10313042

Please see page 3 for packaging details.

Warning: Working Load Limit must not be exceeded. Not to be used for lifting or hoisting applications