



Hot Dip Galvanized Shackles



All of our Titan™ Marine Shackles are Hot Dip Galvanized for premium corrosion resistance. Hot dip galvanized coating on both the shackle & pin.

Finish: Hot Dip Galvanized
 Packaging: Individually labeled
 Exceeds RR-C-271 Type IV Grade A



- Easily identifiable yellow colored pin
- Proof tested & load rated
- Anchor and Chain types
- Working load limit, size, and logo stamped on every shackle

	PID	Specification									
		Size				Working Load Limit			Breaking Load		
		Bail		Pin		kn	lb	kg	kn	lb	kg
		in	mm	in	mm						
Anchor Type	10319050	1/4	6	5/16	8	5	1100	500	30	6600	3000
	10319051	5/16	8	3/8	10	7.5	1650	750	45	9900	4500
	10319052	3/8	10	7/16	11	10	2200	1000	60	13200	6000
	10319053	7/16	11	1/2	13	15	3300	1500	90	19800	9000
	10319054	1/2	13	5/8	16	20	4400	2000	120	26400	12000
	10319055	5/8	16	3/4	19	32.5	7150	3250	195	42900	19500
	10319056	3/4	19	7/8	22	47.5	10450	4750	285	62700	28500
	10319057	7/8	22	1	25	65	14300	6500	390	85800	39000
	10319058	1	25	1 1/8	29	85	18700	8500	510	112200	51000
	10319059	1 1/8	29	1 1/4	32	95	20900	9500	570	125400	57000
	10319060	1 1/4	32	1 3/8	35	120	26400	12000	720	158400	72000
10319061	1 3/8	35	1 1/2	38	135	29700	13500	810	178200	81000	