

SELF-RIGHTING ANCHOR SWIVELS

NEW!



- Flip swivel – rotates anchor into the correct orientation if it retrieves over the bow upside-down
- Covers the size ranges from Rocna®/Vulcan® Anchors 6Kg through 55Kg
- Highest work load of any self-righting swivel on the market
- Will fit imperial and metric chain
- Unique in the market, meets the same load specs even in side load
- Stainless Steel Grade: 17-4PH which is stronger than 316 while still offering excellent corrosion resistance
- Polished mirror finish
- Hardware included: loctite hexagon socket set screws, allen key, installation instructions

The following chain sizes are recommended based on the anchor specifications:

| PID/ DESCRIPTION | LENGTH in | ANCHOR/CHAIN SLOT WIDTH in | ANCHOR SIZE kg | RECOMMENDED G40 CHAIN | WORKING LOAD LIMIT lb |
|--------------------|-----------|----------------------------|------------------------------|----------------------------|-----------------------|
| TS31SU01 Type 1 | 4.2 | 0.56/ 0.39 | Vulcan® & Rocna® 6-15 kg | 1/4", 5/16", 7-8 mm | 3900 |
| TS31SU03 Type 3 | 4.36 | 0.74 / 0.516 | Vulcan® & Rocna® 15-33 kg | 5/16", 3/8", 9-11 mm | 5400 |
| TS31SU05 Type 5 | 5.02 | 0.844 / 0.516 | Vulcan® & Rocna® 25-55 kg | 5/16"-7/16", 10-11 mm * | 7200 |

* Minimum size 5/16" is not recommended, as it is too small a chain for that size of anchor, yet it will fit chains down to 5/16".

Please check manufacturer's specification prior to use. Design subject to change.



ALLMAR.COM.AU

ALL MARINE SPARES

Trade Supplier of the highest quality OEM / Aftermarket Brands